

# PEAK **HIGH SPEED POUCH LAMINATING SYSTEMS**

Peak<sup>®</sup> High Speed pouch laminators feature six rollers for faster lamination.



**CLEARVIEW**<sup>™</sup> see the difference (patent pending)

### **KEY FEATURES**

- Up to 2000mm/79" per minute
- Laminates up to A3/A2 / "Ledger"/"ANSI C"
- Up to 500 micron pouches
- Easy-to-use control panel
- **ClearView<sup>™</sup> panel**
- Auto shut-off

#### **GREAT FOR USE IN**

- In-plant print departments
- Commercial printers
- Instant printers
- **Reprographics**
- Copyshops
- **Schools**
- Colleges

#### **IDEAL WHEN LAMINATING**

- Posters
- Certificates
- Letters
- Legal documents
- Sales Literature

and many more...



Tube





## **Design & Performance**

Mechanical Speed (mm/inches/min)

**Specifications** 

Max. Paper Size Max. Pouch Micron

Number of Rollers

Display

Warranty\*

Warm-up Time (mins)

Power Supply AC (V-Hz) Power Consumption (W)

Laminating Temperature (°C/ °F)

Overall Dimensions (mm/inches) Gross Machine Weight (Kg/lbs)

The Peak® PHS-330 & PHS-450 Pouch Laminators feature a 6 roller design with memory function. They also benefit from our patented user-friendly control panel and a ClearView<sup>™</sup> top panel, allowing you to view the work whilst it laminates.

PHS-450 A2

Ideal for high volume use, the PHS is the unrivalled choice for a busy copyshop or your print department. **Features** 

- ClearView<sup>™</sup> design with hot roller technology
- Energy saving sleep mode
- Six rollers for faster lamination
- Intuitive control panel for ease of use
- Variable temperature controls
- 9 speed operation
- Anti-jam reverse
- LED indicator shows when ready
- Memory function

PHS-450
2000mm/79'

A2/"ANSI C"

500

6

5

0-160 °C/32-320°F

Digital

220/240-50-60

1550

18Kg/40lbs

1 year

innovatelaminate"	888 6
PHS 330	

Intuitive control panel for ease of use

\*For full terms & conditions on parts and labour warranty, visit vivid-online.com/support/warranty\_information Matrix House, Norman Court, Ivanhoe Business Park,

# vivid-online.com

+44 (0)845 1 30 40 50 sales@vivid-online.com

Ashby de la Zouch, Leicestershire LE65 2UZ England

Vivid Laminating Technologies Ltd

PHS-330

2000mm/79"

A3/"Ledger"

500

6

5

0-160 °C/32-320°F

Digital

220/240-50-60

1150

14Kg/31lbs

1 year

550x310x150mm/22x12x6" 700x310x150mm/28x12x6"

Vivid care about the environment and is an ISO 14001 registered company

