

CreaseStream 

Tired with using a **slow performing** desk top creaser?

Now you can crease **6 times faster** with your Card Creaser



6x
FASTER

An affordable solution

Easy to set up and simple to adjust...
The CreaseStream Card Creaser will revolutionise your creasing

It is now possible to manually hand wind up to 2 creases simultaneously through the CreaseStream Card Creaser. This rate easily out performs the manual hand fed matrix creasing units that are currently on the market. The innovative creasing technology used in the CreaseStream Card Creaser will produce excellent quality creasing that eliminates fibre cracking 100% or your money back.

It does this by making use of softer and patented creasing devices that gently manipulate and prepare the area of stock so that cracking does not occur during the folding stage, this will give you the flexibility to produce either 4pp or 6pp book covers, greetings cards, menus, leaflets and brochures etc. Ideally suited for stocks between 100gsm and 350gsm.



Benefits

- Out performs old technology by up to 6 times, or your money back!
- Can process over 6000 creases per hour
- Produces a wider range of quality creases on a full range of digital stocks
- Perfect crease registration, every time
- Can apply two creases simultaneously

Creasing Simplicity


Your CreaseStream Card Creaser is supplied with 4 creasing rib/ ring holders. Each holder can either accommodate the male creasing ribs or the female receiving rings (3 colour coded versions of each are included in the contents).

For precise alignment, fix collar with female ring into position first, and guide male rib into its open channel, before closing and tightening collar hub (see image below). Match the following male/female ribs/rings to achieve correct crease width/depth;

Orange = Paper/Light stocks
100 - 170 gsm

Blue = Medium/Heavy stocks
170 - 300 gsm

Yellow = Heavy stocks
300 - 350 gsm



Machine Specifications

Minimum sheet size:

80 mm x 120 mm

Maximum sheet size:

520 mm x 520 mm

Stock range:

100 - 350 gsm

Machine weight:

16 kg

Dimensions:

Length 730 mm

Width 350 mm

Height 170 mm

